

# Vandal Resistant IR 2CCD Domes

SKD-26R432



## ► Features

- 1/3" SONY CCD and 1/3" SONY Ex-view CCD
- 480 TV Lines / 0.5Lux @F1.2
- IR distance(25-35M)
- Vandalproof and waterproof ,IP65
- Dual MTV 3.6mm IR lens ,have a wide view angle
- Designed as waterproof structure
- Exquisite design ,precise circuit & structure ,incarnated the highest technology
- DC 12V

## SKD-26R432

### ► Specification

<b>Model</b>	SKD-26R432
<b>Signal System</b>	PAL/NTSC
<b>Image Sensor</b>	1/3" Sony CCD(Color) + 1/3" Sony CCD(B / W)
<b>Horizontal Resolution</b>	420 TV Lines / 600 TV Lines
<b>Lens</b>	MTV 3.6 mm IR Lens
<b>Minimum Illumination</b>	0.5Lux/F1.2(LED OFF) ; 0Lux ( LED ON)
<b>Effective Pixels</b>	PAL:752(H)X582(V);NTSC:768(H)X494(V)
<b>S/N Ratio</b>	More than 52dB
<b>Electronic Shutter</b>	1/50~1/100,000sec(PAL),1/60~1/100,000sec(NTSC)
<b>White Balance</b>	Automatic
<b>AGC/BLC</b>	Automatic
<b>IR series distance</b>	25~30 Meter
<b>View angle</b>	60°
<b>LED wave length</b>	36 units 850nm Infrared LED
<b>Average life</b>	20000hrs,warranty life:6000hrs
<b>Water resistance</b>	IP65
<b>Video Output</b>	Composite Video Output(1.0Vp-p 75ΩTerminated)
<b>Power Supply</b>	DC 12V 450mA(+/-10%)
<b>Operation Temperature</b>	-20°C ~ 50°C (-4°F ~ 122°F)
<b>Body</b>	Aluminum
<b>Weight</b>	1100g

### ► Dimension

