

Vandal Resistant IR Dome Cameras

SKD-26F532



SKD-26F536



► Features

- | | |
|----------------------------------|---------|
| • SKD-26F532: | Value |
| 1/3" SONY SUPER HAD CCD | • DC12V |
| 420 TV Lines / 0.5Lux @F1.2 | |
| • SKD-26F536 : | |
| 1/3" SONY SUPER HAD CCD | |
| SONY 10-bit HQ1 DSP | |
| 530 TV Lines / 0.8Lux @F1.2 | |
| • DSP technology | |
| • BLC, AES, AGC, AWB | |
| • 14 High Intensity LED | |
| • Built-in 3.6mm Lens, excellent | |

SKD-26F532 / SKD-26F536

► Specification

Model	SKD-26F532	SKD-26F536
CCD	1/3" SONY SUPER HAD CCD	1/3" SONY SUPER HAD CCD
DSP	SONY DSP	SONY 10-bit HQ1 DSP
Effective pixels	PAL:500(H)x582(V) NTSC:510(H)x492(V)	PAL:752(H)x582(V) NTSC:768(H)x494(V)
Signal System	PAL/NTSC	
Horizontal Resolution	420 TV Lines	530 TV Lines
Lens	3.6mm Fixed Lens	
Sync. System	Internal	
Minimum Illumination	0.5Lux @F1.2	0.8Lux @F1.2
S/N Ratio	More than 48dB(AGC OFF)	
Electronic Shutter	PAL:1/50(1/60)~1/12000sec.	
White Balance	Auto	
Backlight Compensation	Auto	
Auto Gain Control	Auto	
Video Output	Composite Video Output(1Vp-p 75ΩTerminated)	
Power Sourcing	DC12V / 350mA	
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F) RH95%(MAX)	

► Dimension

