

SS-HDR-8604/8608/8616

H.264 Real-time Standalone DVR



Specifications

Model	SS-HDR-8604	SS-HDR-8608	SS-HDR-8616
Video			
Video format	NTSC / PAL		
Analog video input	1.0V/p-p/75Ω,BNCx4	1.0V/p-p/75Ω,BNCx8	1.0V/p-p/75Ω,BNCx16
CVBS output	1CH (BNC)		
VGA output	1280 x 1024		
Synchronous playback	4CH Simultaneously(D1:1CH)	8CH Simultaneously	16CH Simultaneously
Playback frame rate	CIF(352*288),D1(704*576)	CIF(352*288),D1(704*576)	CIF(352*288),D1(704*576)
Record frame rate	D1:100fps(PAL),120fps(NTSC) CIF:100fps(PAL),120fps(NTSC)	D1:100fps(PAL), 120fps(NTSC) CIF:200fps(PAL), 240fps(NTSC)	D1:100fps(PAL), 120fps(NTSC) CIF:400fps(PAL), 480fps(NTSC)
Record mode	Timer / Motion detection		
Other Function			
Audio input / output	4CH / 1CH	4CH / 1CH	4CH / 1CH
Alarm input /output	4CH / 1CH	4CH / 1CH	4CH / 1CH
Mechanical			
Simplex/multiplex	Multiplex		
Network port	RJ45		
PTZ	RS485		
USB port	2* USB 2.0 host		
Hard disk	1*SATA HDDs (Max. 2 TB)		
Remote controller	Yes		
Operating temperature	(-10°C~+50°C)		
Power supply	DC 12V/3A		
Weight	About 3 kg with package		
External Dimension(mm)	340*265*68mm		

Feature

- 1280*1024 HD Live-Display Resolution
- Low power consumption, strong performance, superior video quality.
- Top advanced arithmetic: H.264 video compression.
- 4/8 CH playback simultaneously.
- 4 CH Audio & Video Synchronization.
- Remote monitoring through IE. Mobile or free CMS software, CMS for 256 CH management.
- 2 USB Interface.
- Lightning protection up to 6000V to ensure higher stability
- Support External USB-Interfaced DVD-RW Writer

Dimension(unit:mm)



J&S United Technology Corp.
13F-6, No. 258, Lian-Cheng Rd., Chung-Ho City, Taipei County 235, Taiwan
TEL.: +886-2-8227-2528 FAX: +886-2-8227-2338
www.jsccctv.com.tw

