

H.264 Real-time Standalone DVR

H.264



► Features

- HDMI/ YPbPr :1920x1080
- VGA :1280x1024
- 16CH playback simultaneously
- 16CH audio supported
- 4* 2000G HDD supported

SS-HDR-8904 / SS-HDR-8908 / SS-HDR-8916

► Specification

Model	SS-HDR-8904	SS-HDR-8908	SS-HDR-8916
Video format	NTSC / PAL		
Video input	1.0V/p-p/75Ω,BNCx4	1.0V/p-p/75Ω,BNCx8	1.0V/p-p/75Ω,BNCx16
Video output	1.0V p-p/75Ω, BNCx1, VGAX1		
LPOT output	1.0V/p-p/75Ω,BNCx4	1.0V/p-p/75Ω,BNCx8	1.0V/p-p/75Ω,BNCx16
SPOT output	1.0V p-p/75Ω BNCX1		
YPdPr output resolution	1920x1080i50 / 1920x1080i60		
HDMI output resolution	1920x1080i50 / 1920x1080i60		
VGA output resolution	1280x1024		
Record resolution CIF	Not support	8CH Realtime	16CH Realtime
Record resolution D1	4CH Realtime	8CH Realtime	6 fps/channel
Record mode	Sensor / Timer / Motion detection		
play back	4CH Simultaneously	8CH Simultaneously	16CH Simultaneously
Audio input / output	4CH/1CH	8CH/1CH	16CH/1CH
Alarm input	4	8	16
Alarm output	Relay output, NO(Normal open), NC(Normal close), COM		
Alarm trigger	Sensor alarm; motion detection alarm;video loss alarm; disk full alarm		
Network resolution/fps	CIF each channel >20 fps		
Mobile	Windows mobile, Symbian iPhone		
Mouse	YES		
Network port	RJ45		
PTZ	RS485		
USB port	Two USB 2.0host		
Hard disk	Support 4*2000G SATA HDD		
DVD-RW	Optional		
Remote controller	YES		
Power supply	220V / 110V		
Power	Lower then 12W (without HDD)		
Weight	About 8kg with package		
External Dimension(mm)	435mm(L)x415mm(W)x103mm(H)		