

# SS-HDR-8904/8908/8916

H.264 Real-time Standalone DVR



## Specifications



## Feature

- Low power consumption, strong performance,
- Superior video quality
- H.264 video compression
- HDMI / YPbPr : 1920 x 1080i
- 4/8/16 CH Looping output
- 4/8/16 CH audio supported
- 4/8/16 CH alarm input
- CMS software (Central Management System)
- 2 USB Interface
- Simplest DDNS
- 16CH playback supported

| Model                            | SS-HDR-8904   | SS-HDR-8908   | SS-HDR-8916  |
|----------------------------------|---|---|--|
| <b>Video</b>                     |   |   |  |
| Video format                     | NTSC / PAL  |   |  |
| Video input                      | 1.0V/p-p/75Ω,BNCx4  | 1.0V/p-p/75Ω,BNCx8  | 1.0V/p-p/75Ω,BNCx16  |
| Video output                     | 1.0V p-p/75Ω, BNCx1, VGAX1 (1280x1024)                                    |   |  |
| VGA output                       | 1CH, 1280 x 1024  |   |  |
| Matrix output                    | 1.0V p-p/75Ω, BNCx4   | 1.0V/p-p/75Ω,BNCx8  | 1.0V p-p/75Ω, BNCx16   |
| YPbPr output                     | 1920 x 1080i / 60Hz   |   |  |
| HDMI output                      | 1 CH ,1920 x 1080i / 60Hz   |   |  |
| <b>Recording / Play Function</b> |   |   |  |
| Synchronous playback             | 4CH Simultaneously  | 8CH Simultaneously  | 16CH Simultaneously  |
| Playback frame rate              | D1(704*576)   | CIF(352*288),D1(704*576)                                    | CIF(352*288),D1(704*576)                                     |
| Record frame rate                | D1:100fps(PAL),120fps (NTSC)  | D1:200fps(PAL),240fps(NTSC)<br>CIF:200fps(PAL),240fps(NTSC) | D1:100fps(PAL),120fps (NTSC)<br>CIF:400fps(PAL),480fps(NTSC) |
| Record mode                      | Sensor / Timer / Motion detection   |   |  |
| <b>Other Function</b>            |   |   |  |
| Audio input / output             | 4CH / 1CH   | 8CH / 1CH   | 16CH / 1CH   |
| Alarm input                      | 4 CH  | 8 CH  | 16 CH  |
| Alarm output                     | Relay output, NO, NC, COM   |   |  |
| Alarm trigger                    | Sensor alarm, Motion detection alarm , Video loss alarm , Disk full alarm |   |  |
| <b>Mechanical</b>                |   |   |  |
| Simplex/multiplex                | Multiplex   |   |  |
| Network port                     | RJ45  |   |  |
| PTZ                              | RS485   |   |  |
| USB port                         | 2 * USB 2.0 host  |   |  |
| Hard disk                        | 4 * SATA HDDs (Max. 2 TB) or 1 * DVD-RW + 3 *SATA HDDs                    |   |  |
| DVD-RW                           | Optional  |   |  |
| Remote controller                | Yes   |   |  |
| Power supply                     | 220V/110V   |   |  |
| Power                            | Lower than 12W (without HDD)  |   |  |
| Weight                           | About 7.5kg with package  |   |  |
| External Dimension(mm)           | 435(L)x415(W)x103(H)  |   |  |



J&S United Technology Corp.  
13F-6, No. 258, Lian-Cheng Rd., Chung-Ho City, Taipei County 235, Taiwan  
TEL: +886-2-8227-2528 FAX: +886-2-8227-2338  
www.jsccctv.com.tw

