

SS-HDR-8916D 8928D

H.264 D1 Real-time DVR



Specifications



Featurese

- Support YPBPr or HDMI output , connected with big size HD TV perfectly, resolution is 1920x1080.
- Up to 28 channels D1 Real-time recording and 4 channels playback at the same time.
- Supply BUILT-IN DDNS domain name.
- Support Five OS for mobile surveillance.
- Powerful CMS.
- Support 16 users network view simultaneously.

Model	SS-HDR-8928D	SS-HDR-8916D
Video		
Video format	NTSC / PAL	
Video input	1.0V/p-p/75Ω,BNCx28	1.0V/p-p/75Ω,BNCx16
Video output	1.0V p-p/75Ω, BNCx1, VGAX1 (1280x1024)	
Looping output	Not support	1.0V/p-p/75Ω,BNCx16
YPbPr output	1920 x 1080i 50 / 1920 x 1080i 60	
HDMI output	1920 x 1080i 50 / 1920 x 1080i 60	
VGA output resolution	1280 x 1024	
Recording / Play Function		
Playback frame rate	D1(407*576)	D1(407*576)
Network frame rate / fps	CIF each channel 25 fps	
Record frame rate	D1 realtime: 700 fps(PAL) ,840 fps(NTSC)	D1 realtime: 400 fps(PAL) ,480 fps(NTSC)
Record mode	Sensor / Time / Motion detection	
Other Function		
Audio input / output	16CH / 1CH	
Alarm input	16 CH	16 CH
Alarm output	Relay output, NO, NC, COM	
Alarm trigger	Sensor input alarm, Disk full alarm, Motion detection alarm , Video loss alarm	
Mechanical		
Simplex/multiplex	Multiplex	
Network port	RJ45	
PTZ	RS485	
USB port	2* USB 2.0 host	
Hard disk	7*SATA HDDs (Max. 2 TB)	
DVD-RW	Optional	
Remote controller	Yes	
Power supply	220V/110V	
Power	Lower then 12W (without HDD)	
Weight	About 8kg with package	
External Dimension(mm)	435(L)x415(W)x100(H)	



J&S United Technology Corp.
13F-6, No. 258, Lian-Cheng Rd., Chung-Ho City, Taipei County 235, Taiwan
TEL.: +886-2-8227-2528 FAX: +886-2-8227-2338
www.jsccctv.com.tw

