

SS-HDR-8924/8932C

H.264 Stand-Alone DVR



Specifications

Model	SS-HDR-8924	SS-HDR-8932C
Video		
Video format	NTSC / PAL	
Video input	1.0V/p-p/75Ω, BNCx24	1.0V/p-p/75Ω, BNCx32
Video output	1.0V p-p/75Ω, BNCx1, VGAX1 (1280x1024)	
YPbPr output	1920 x 1080i 50 / 1920 x 1080i 60	
HDMI output	1920 x 1080i 50 / 1920 x 1080i 60	
VGA output resolution	1280 x 1024	
Recording / Play Function		
Playback frame rate	CIF(352*288),D1(704*576)	16CH Simultaneously(with 4Ch D1 Playback)
Network frame rate / fps	CIF each channel 25 fps	
Record frame rate	D1not realtime: 150 fps(PAL),150 fps(NTSC) CIF realtime: 600 fps(PAL) ,720 fps(NTSC)	D1 not realtime: 200 fps(PAL),200 fps(NTSC) CIF realtime: 800 fps(PAL) ,960 fps(NTSC)
Record mode	Sensor / Time / Motion detection	
Other Function		
Audio input / output	4CH/1CH	8CH/1CH
Alarm input	16 CH	16 CH
Alarm output	Relay output, NO, NC, COM	
Alarm trigger	Sensor input alarm, Disk full alarm, Motion detection alarm, Video loss alarm	
Mechanical		
Simplex/multiplex	Multiplex	
Network port	RJ45	
PTZ	RS485	
USB port	2* USB 2.0 host	
Hard disk	4*SATA HDDs (Max. 2 TB)	7*SATA HDDs (Max. 2TB)
DVD-RW	Optional	
Remote controller	Yes	
Power supply	220V/110V	
Power	Lower then 12W (without HDD)	
Weight	About 8kg with package	
External Dimension(mm)	435(L)x415(W)x100(H)	

Feature

- Low power consumption, strong performance, superior video quality
- H.264 video compression
- HDMI / YPbPr : 1920*1080
- Audio supported
- With Alarm in/out function
- CMS software (Central Management System)
- 2 USB Interface
- Simplest DDNS
- 16CH playback supported
- Support External USB-Interfaced DVD-RW Writer



J&S United Technology Corp.
13F-6, No. 258, Lian-Cheng Rd., Chung-Ho City, Taipei County 235, Taiwan
TEL.: +886-2-8227-2528 FAX: +886-2-8227-2338
www.jscctv.com.tw

