

SSV-732S / SSV-732HI / SSV-732I

1/4" 25M Color IR Dome with 2.8mm Lens



Specifications

Model	SSV-732S	SSV-732HI	SSV-732I
Image			
Divice	1/4"SHARP CCD	1/3" High Res.Sharp CCD	1/3" Sharp CCD
Size	1/4"	1/3"	1/3"
Pixels(HxV)	NTSC: 510(H)*492(V)/ PAL: 500(H)*582(V)	NTSC:768(H) x 492(V), PAL:752(H) x 582(V)	NTSC: 510(H)*492(V)/ PAL: 500(H)*582(V)
Resolution	420 TVL	520TVL	420 TVL
Min.Scene Illumination			
Color	0.01 Lux @F2.0 / 0 Lux (LED ON)		
B/W	N/A		
Lens			
Focal Lenght	2.8 mm Lens		
Synchronization			
Sync. System	2:1 Interlace		
S/N Ratio			
S/N Ratio	52 dB (AGC off)		
Functions			
Electronic Shutter	Auto: 1/50(60) ~1/100,000 sec		
Mechanical IR Cut Filter	400~645nm+850nm		
Video Output	1.0 Vp-p Composite Video Output ; 75 Ohm		
CDS Control	Minus Delta Voltage		
Auto Gain Control	Auto		
IR LED	32*IR-LEDs		
Illuminate Distance	25M		
Environmental			
Operating Temperature	- 10°C~ + 50°C degree		
Power			
Power Consumption	DC 12V /3.5W		

Feature

- SHARP CCD
- 420 / 520TVL
- 0.01 Lux @F2.0 / 0 Lux (LED ON)
- YC separation circuit design
- Double Glass Lens for Avoiding Halos & Blur
- High Power IR LEDs Adjustments
- Auto Gain Control
- DC12V

Dimension(unit:mm)



J&S United Technology Corp.
13F-6, No. 258, Lian-Cheng Rd., Chung-Ho City, Taipei County 235, Taiwan
TEL.: +886-2-8227-2528 FAX: +886-2-8227-2338
www.jscctv.com.tw

