

SSV-732 / SSV-732HQ

1/3" 25M Color IR Dome



Specifications

Model	SSV-732	SSV-732HQ
Image		
Device	1/3" SONY CCD	1/3" High Res.Sony CCD
Size	1/3"	
Pixels(HxV)	NTSC: 510(H)*492(V) PAL: 500(H)*582(V)	NTSC: 768(H) x 492(V) PAL :752(H) x 582(V)
Resolution	420 TVL	540 TVL
Min.Scene Illumination		
Color	0.01 Lux @F2.0 / 0 Lux (LED ON)	
B/W	N/A	
Lens		
Focal Length	4 mm Board Lens	
Synchronization		
Sync. System	2:1 Interlace	
S/N Ratio		
S/N Ratio	More than 48 dB	
Functions		
Electronic Shutter	Auto: 1/50(60) ~1/100,000 sec	
Mechanical IR Cut Filter	400~645nm+850nm	
Video Output	1.0 Vp-p Composite Video Output ; 75 Ohm	
CDS Control	Minus Delta Voltage	
Auto Gain Control	Auto	
IR LED	32*IR-LEDs	
Illuminate Distance	25M	
Environmental		
Operating Temperature	- 10°C~ + 50°C degree	
Power		
Power Consumption	DC 12V /3.5W	

Feature

- 1/3" SONY CCD
- 420 / 540 TVL
- 0.01 Lux @F2.0 / 0 Lux (LED ON)
- High sensitivity and
- ATW With Mct Technology (Multi-Color
- Temp)
- Auto Gain Control
- DC12V
- YC separation circuit design
- Double Glass Lens for Avoiding Halos & Blur
- High Power IR LEDs Adjustments

Dimension(unit:mm)



J&S United Technology Corp.
13F-6, No. 258, Lian-Cheng Rd., Chung-Ho City, Taipei County 235, Taiwan
TEL.: +886-2-8227-2528 FAX: +886-2-8227-2338
www.jsctv.com.tw

