

SSV-805S / SSV-805HI / SSV-805I

Color Smoke Detector Covert Camera



Specifications




Model	SSV-805S	SSV-805HI	SSV-805I
Image			
Divice	1/4" Sharp CCD	1/3" High Res. Sharp CCD	1/3" Sharp CCD
Pixels(HxV)	NTSC: 510(H)*492(V)/ PAL: 500(H)*582(V)	NTSC:768(H) * 492(V)/ PAL:752(H)*582(V)	NTSC: 510(H)*492(V)/ PAL: 500(H)*582(V)
Resolution	420 TVL	520 TVL	420 TVL
Min.Scene Illumination			
Color	0.5 Lux		
B/W	N/A		
Lens			
Focal Lenght	3.6mm Lens		
Synchronization			
Sync. System	2:1 Interlace		
S/N Ratio			
S/N Ratio	More than 48dB		
Functions			
Electronic Shutter	Auto: 1/50(60) ~1/100,000 sec		
Video Output	1.0 Vp-p Composite Video Output ; Ohm		
Auto White Balance	Auto(2500K-9500K)		
Auto Gain Control	Auto		
Environmental			
Operating Temperature	- 10°C~ + 50°C degree		
Power			
Power Consumption	DC 12V (-/+10%)		

Feature

- Sharp CCD
- 0.5 Lux / F2.0
- 3.6mm Lens
- ATW With MCT Technology (Multi-Color Temp)
- Auto Gain Control
- Auto Back Light Compensation
- DC12V

Dimension(unit:mm)



J&S United Technology Corp.
13F-6, No. 258, Lian-Cheng Rd., Chung-Ho City, Taipei County 235, Taiwan
TEL.: +886-2-8227-2528 FAX: +886-2-8227-2338
www.jsccctv.com.tw

