

SSV-806 / SSV-806HQ

1/3" Color Dome Camera



Specifications




Model	SSV-806	SSV-806HQ
Image		
Device	1/3" SONY CCD	1/3" High Res.Sony CCD
Size	1/3"	
Pixels(HxV)	NTSC: 512(H)*492(V)/PAL :512(H)*582(V)	NTSC: 768(H) x 492(V)/PAL :752(H) x 582(V)
Resolution	420 TVL	540 TVL
Min.Scene Illumination		
Color	0.5Lux @F2.0	0.2 Lux @F2.0
B/W	N/A	
Lens		
Focal Lenght	3.6 mm Lens	
Synchronization		
Sync. System	2:1 Interlace	
S/N Ratio		
S/N Ratio	More than 48dB	
Functions		
Electronic Shutter	Auto 1/60(50)sec. ~ 100,000 sec.	
Auto White Balance	Atw With Mct Technology (Multi-Color Temp)	
Auto Gain Control	Full Auto	
Video Output	1.0 Vp-p Composite Video Output/Ohms	
Gamma	0.45	
Environmental		
Operating Temperature	- 10°C~ + 50°C degree	
Conditions		
Operationg Humidity	RH 85% or Less	
Power		
Power Consumption	100mA ±10% under DC 12V	
Power Supply	DC 12V (-/+10%)	
Physical Specification		
Dimensions	58mm*87mm	

Feature

- 1/3" SONY CCD
- 420 /540TVL
- 0.5 / 0.2 TVL
- 3.6mm Lens
- ATW With MCT Technology (Multi-Color Temp)
- Auto Gain Control
- Auto Back Light Compensation
- 2H Mode of H.V aperture correction
- DC12V

Dimension(unit:mm)



More information is available at www.jsctv.com



J&S United Technology Corp.
13F-6, No. 258, Lian-Cheng Rd., Chung-Ho City, Taipei County 235, Taiwan
TEL: +886-2-8227-2528 FAX: +886-2-8227-2338
www.jsctv.com.tw

