

# SSV-924S / SSV-924I / SSV-924HI

Vandal-proof 20M Color IR Dome



## Specifications

Model	SSV-924S	SSV-924HI	SSV-924I
<b>Image</b>			
Divice	1/4" SHARP CCD	1/3" High Res. Sharp CCD	1/3" Sharp CCD
Size	1/4"		
Pixels(HxV)	NTSC: 510(H) x 492(V) PAL: 500(H) x 582(V)	NTSC: 768(H) x 492(V), PAL: 752(H) x 582(V)	NTSC: 510(H) x 492(V) PAL: 500(H) x 582(V)
Resolution	420 TVL	520 TVL	420 TVL
<b>Min. Scene Illumination</b>			
Color	0.01 Lux @F2.0 / 0 Lux (LED ON)		
B/W	N/A		
<b>Lens</b>			
Focal Length	4 mm Lens		
<b>Synchronization</b>			
Sync. System	2:1 Interlace		
<b>S/N Ratio</b>			
S/N Ratio	52 dB (AGC off)		
<b>Functions</b>			
Electronic Shutter	Auto: 1/50(60) ~ 1/100,000 sec		
Mechanical IR Cut Filter	400 ~ 645nm + 850nm		
Video Output	1.0 Vp-p Composite Video Output ; 75 Ohm		
CDS Control	Minus Delta Voltage		
Auto Gain Control	Auto		
IR LED	24*IR-LEDs		
Illuminate Distance	20M		
<b>Environmental</b>			
Operating Temperature	- 10°C ~ + 50°C degree		
<b>Power</b>			
Power Consumption	DC 12V / 3.5W		

## Feature

- SHARP CCD
- 420 / 520 TVL
- 0.01 Lux @F2.0 / 0 Lux (LED ON)
- High sensitivity and
- ATW With Mct Technology (Multi-Color
- Temp)
- Auto Gain Control
- DC12V

## Dimension(unit:mm)



J&S United Technology Corp.  
13F-6, No. 258, Lian-Cheng Rd., Chung-Ho City, Taipei County 235, Taiwan  
TEL.: +886-2-8227-2528 FAX: +886-2-8227-2338  
www.jsctv.com.tw

