

SSV-936SVF / SSV-936HIVF / SSV-936IVF

Vandal-proof 30M Color IR Dome



Specifications

Model	SSV-936SVF	SSV-936HIVF	SSV-936IVF
Image			
Device	1/4" Sharp CCD	1/3" Sharp CCD	1/3" Sharp CCD
Pixels(HxV)	NTSC: 510(H)*492(V)/ PAL: 500(H)*582(V)	NTSC:768(H) * 492(V)/ PAL:752(H)*582(V)	NTSC: 510(H)*492(V)/ PAL: 500(H)*582(V)
Resolution	420 TVL	520 TVL	420 TVL
Min.Scene Illumination			
Color	0.01 Lux @F2.0 / 0 Lux (LED ON)		
B/W	N/A		
Lens			
Focal Length	4-9 mm Lens		
Synchronization			
Sync. System	2:1 Interlace		
S/N Ratio	More than 48dB		
Functions			
Electronic Shutter	Auto: 1/50(60) ~1/100,000 sec		
Mechanical IR Cut Filter	400~645nm+850nm		
Video Output	1.0 Vp-p Composite Video Output ; Ohm		
Auto White Balance	Auto(2500K-9500K)		
Auto Gain Control	Auto		
IR LED	36 x IR-LED		
Illuminate Distance	30M		
Illuminator Active Limit	10lux		
Environmental			
Operating Temperature	- 10°C~ + 50°C degree		
Power			
Power Consumption	DC 12V (-/+10%)		

Feature

- 1/3" Sharp CCD
- 420 / 520 / 420TVL
- 0.01 Lux @F2.0 / 0 Lux (LED ON)
- YC separation circuit design
- High Power IR LEDs Adjustments
- Auto Gain Control
- DC12V
- Double Glass Lens for Avoiding Halos & Blur

Dimension(unit:mm)



J&S United Technology Corp.
13F-6, No. 258, Lian-Cheng Rd., Chung-Ho City, Taipei County 235, Taiwan
TEL.: +886-2-8227-2528 FAX: +886-2-8227-2338
www.jsccctv.com.tw

