

SSV-936 / SSV-936HQ

Vandal-proof 30M Color IR Dome



Specifications



Model	SSV-936	SSV-936HQ
Image		
Divice	1/3" SONY CCD	1/3" High Res.SONY CCD
Size		
Size	1/3"	
Pixels(HxV)	NTSC: 512(H)*492(V)/PAL :512(H)*582 (V)	
Resolution	420 TVL	540TV
Min.Scene Illumination		
Color	0.01 Lux @F2.0 / 0 Lux (LED ON)	
B/W	N/A	
Lens		
Focal Lenght	4 mm Lens	
Synchronization		
Sync. System	2:1 Interlace	
S/N Ratio		
S/N Ratio	More than 48dB	
Functions		
Electronic Shutter	Auto 1/60(50)sec. ~ 100,000 sec.	
Auto White Balance	Atw With Mct Technology (Multi-Color Temp)	
Auto Gain Control	Full Auto	
Video Output	1.0 Vp-p Composite Video Output/Ohms	
Gamma	0.45	
IR LED		
IR LED	36 x IR-LED	
Illuminate Distance	30M	
Illuminator Active Limit	10lux	
Environmental		
Operating Temperature	- 10°C~ + 50°C degree	
Conditions		
Operating Humidity	RH 85% or Less	
Power		
Power Consumption	100mA ±10% under DC 12V	
Power Supply	DC 12V (-/+10%)	

Feature

- 1/3" SONY CCD
- 420 / 540 TVL
- ATW With MCT Technology (Multi-Color Temp)
- Auto Gain Control
- Auto Back Light Compensation
- 2H Mode of H.V aperture correction
- DC12V

Dimension(unit:mm)



J&S United Technology Corp.
13F-6, No. 258, Lian-Cheng Rd., Chung-Ho City, Taipei County 235, Taiwan
TEL.: +886-2-8227-2528 FAX: +886-2-8227-2338
www.jsctv.com.tw

