

SSV-D1101S / SSV-D1101HI / SSV-D1101I

Color 3-Axis Dome Camera



3-Axis Mechanism

Feature

- Sharp CCD
- 420 / 520 TVL
- 0.5 Lux / F2.0
- AWB
- Auto Gain Control
- DC12V
- 3-Axis Adjustment Design

Specifications

Model	SSV-D1101S	SSV-D1101HI	SSV-D1101I
Image			
Divice	1/4" SHARP	1/3" High Res.Sharp CCD	1/3" Sharp CCD
Size	1/4"	1/3"	1/3"
Pixels(HxV)	NTSC: 510(H) x 492(V)/PAL :500(H) x 582(V)	NTSC:768(H) x 492(V), PAL:752(H)x 582(V)	NTSC: 510(H) x 492(V)/ PAL :500(H) x 582(V)
Resolution	420 TVL	520 TVL	420 TVL
Min.Scene Illumination			
Color	0.5 Lux @F2.0		
B/W	N/A		
Lens			
Focal Length	2.8 mm Lens	3.6 mm Lens	
Synchronization			
Sync. System	2:1 Interlace		
S/N Ratio			
S/N Ratio	48 dB (AGC OFF)		
Functions			
Electronic Shutter	Auto 1/60(50)sec. ~ 100,000 sec.		
Auto White Balance	Auto(2500K-9500K)		
Auto Gain Control	Full Auto		
Video Output	1.0 Vp-p Composite Video Output/Ohms		
Gamma	0.45		
Environmental			
Operating Temperature	- 10°C~ + 50°C degree		
Conditions			
Operationg Humidity	RH 85% or Less		
Power			
Power Supply	DC 12V / 3.5W		

Dimension(unit:mm)



J&S United Technology Corp.
13F-6, No. 258, Lian-Cheng Rd., Chung-Ho City, Taipei County 235, Taiwan
TEL.: +886-2-8227-2528 FAX: +886-2-8227-2338
www.jsctv.com.tw

