

Vandal-Proof Dome Cameras



Model	SKD-27KB21	SKD-27KB23	SKD-27KB32	SKD-27C621	SKD-27C632	SKD-27C634	SKD-27C636	SKD-27C630	SKD-27F532	SKD-27F536	SKD-27C321	SKD-27C332	SKD-27C334	SKD-27C336	SKD-27C330	
Image Sensor	1/4" Sharp CCD	1/3" Sony Super HAD CCD	1/3" Sony Exview CCD	1/4" Sharp CCD	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD	1/3" Sony Exview CCD	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD	1/4" Sharp CCD	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD	1/3" Sony Exview CCD	
DSP	Sharp DSP	Sony DSP	Sony DSP	Sharp DSP	Sony DSP	Sony DSP	Sony 10-bit HQ1 DSP	Nextchip DSP	Sony DSP	Sony 10-bit HQ1 DSP	Sharp DSP	Sony DSP	Sony DSP	Sony 10-bit HQ1 DSP	Nextchip DSP	
Effective pixels	PAL:542(H) x582(v) NTSC:512(H) x492(v)	PAL:537(H) x597(v) NTSC:537(H) x505(v)	PAL:795(H) x596(v) NTSC:811(H) x508(v)	PAL:512(H) x582(v) NTSC:512(H) x492(v)	PAL:500(H) x582(v) NTSC:510(H) x492(v)	PAL:752(H) x582(v) NTSC:768(H) x494(v)	PAL:795(H) x596(v) NTSC:811(H) x508(v)	PAL:795(H) x596(v) NTSC:811(H) x508(v)	PAL:795(H) x596(v) NTSC:811(H) x508(v)	PAL:500(H) x582(V) NTSC:512(H) x492(V)	PAL:752(H) x582(V) NTSC:768(H) x494(V)	PAL:512(H) x582(v) NTSC:512(H) x492(v)	PAL:500(H) x582(v) NTSC:510(H) x492(v)	PAL:752(H) x582(v) NTSC:768(H) x494(v)	PAL:795(H) x596(v) NTSC:811(H) x508(v)	PAL:795(H) x596(v) NTSC:811(H) x508(v)
Signal System	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	
Horizontal Resolution	420 TV Lines	420 TV Lines	480 TV Lines	420 TV Lines	420 TV Lines	480 TV Lines	540 TV Lines	520 TV Lines	420 TV Lines	530 TV Lines	420 TV Lines	420 TV Lines	480 TV Lines	540 TV Lines	520 TV Lines	
Lens	3.6mm Lens	3.6mm Lens	3.6mm Lens	4-9.0 mm Auto Iris Lens	4-9.0 mm Auto Iris Lens	4-9.0 mm Auto Iris Lens	4-9.0 mm Auto Iris Lens	4-9.0 mm Auto Iris Lens	4-9.0 mm Auto Iris Lens	4-9.0mm Auto Iris Lens	4-9.0 mm Auto Iris Lens	4-9.0 mm Auto Iris Lens	4-9.0 mm Auto Iris Lens	4-9.0 mm Auto Iris Lens	4-9.0 mm Auto Iris Lens	
Sync. System	Internal	Internal	Internal	Internal	Internal	Internal	Internal	Internal	Internal	Internal	Internal	Internal	Internal	Internal	Internal	
Minimum Illumination	1.0LUX@F1.2	0.8LUX@F1.2	0.8Lux@F1.2	1.0LUX@F1.2	0.5LUX@F1.2	0.8Lux@F1.2	0.8Lux@F1.2	0.8Lux@F1.2	0.5Lux @F1.2	0.8Lux @F1.2	1.0LUX@F1.2	0.8LUX@F1.2	0.8Lux@F1.2	0.8Lux@F1.2	0.8Lux@F1.2	
S/N Ratio	More than 48dB	More than 48dB	More than 48dB	More than 48dB	More than 48dB	More than 48dB	More than 48dB	More than 48dB	More than 48dB	More than 48dB	More than 48dB	More than 48dB	More than 48dB	More than 48dB	More than 48dB	
Shutter Speed	Auto:1/50(1/60)— 1/100,000(1/100,000)(Sec.)	Auto:1/50(1/60)— 1/100,000(1/100,000)(Sec.)	Auto:1/50(1/60)— 1/100,000(1/100,000)(Sec.)	Auto:1/50(1/60)— 1/100,000(1/100,000)(Sec.)	Auto:1/50(1/60)— 1/100,000(1/100,000)(Sec.)	Auto:1/50(1/60)— 1/100,000(1/100,000)(Sec.)	Auto:1/50(1/60)— 1/100,000(1/100,000)(Sec.)	Auto:1/50(1/60)— 1/100,000(1/100,000)(Sec.)	Auto:1/50(1/60)— 1/100,000(1/100,000)(Sec.)	Auto:1/50(1/60)— 1/100,000(1/100,000)(Sec.)	Auto:1/50(1/60)— 1/100,000(1/100,000)(Sec.)	Auto:1/50(1/60)— 1/100,000(1/100,000)(Sec.)	Auto:1/50(1/60)— 1/100,000(1/100,000)(Sec.)	Auto:1/50(1/60)— 1/100,000(1/100,000)(Sec.)	Auto:1/50(1/60)— 1/100,000(1/100,000)(Sec.)	
White Balance	ATW / AWC	ATW / AWC	ATW / AWC	ATW	ATW	ATW	ATW	ATW	ATW	Auto	Auto	ATW	ATW	ATW	ATW	
Gain Control	On/Off	On/Off	On/Off	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	
Backlight Compensation	On/Off	On/Off	On/Off	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	
Video Output	1Vp- p,75ohm,BNC	1Vp- p,75ohm,BNC	1Vp- p,75ohm,BNC	1Vp- p,75ohm,BNC	1Vp- p,75ohm,BNC	1Vp- p,75ohm,BNC	1Vp- p,75ohm,BNC	1Vp- p,75ohm,BNC	1Vp- p,75ohm,BNC	1Vp- p,75ohm,BNC	1Vp- p,75ohm,BNC	1Vp- p,75ohm,BNC	1Vp- p,75ohm,BNC	1Vp- p,75ohm,BNC	1Vp- p,75ohm,BNC	
Power Sourcing	DC12V	DC12V	DC12V	DC12V	DC12V	DC12V	DC12V	DC12V	DC12V	DC12V	DC12V	DC12V	DC12V	DC12V	DC12V	
Current Consumption	-	-	-	120mA	120mA	120mA	120mA	120mA	-	-	120mA	120mA	120mA	120mA	120mA	
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	-10°C ~ 50°C (14°F ~ 122°F)	
Dimension (mm)	108 (Dia.) * 70 (H)	108 (Dia.) * 70 (H)	108 (Dia.) * 70 (H)	155 (Dia.) * 115 (H)	155 (Dia.) * 115 (H)	155 (Dia.) * 115 (H)	155 (Dia.) * 115 (H)	155 (Dia.) * 115 (H)	155 (Dia.) * 115 (H)	118 (Dia.) * 96 (H)	118 (Dia.) * 96 (H)	155 (Dia.) * 115 (H)	155 (Dia.) * 115 (H)	155 (Dia.) * 115 (H)	155 (Dia.) * 115 (H)	